



PURPOSE AV - 4MP, EXIR BULLET, OUTDOOR, 2.8MM

SKU: HNC324-XB

FEATURES

- » 4 MP High Resolution
- » Full HD 4 MP Video Output
- » Low Illumination
- » 3D DNR; True WDR; BLC
- » IP67 Rating
- » IR Range: upto 150 ft
- » True Day/Night
- » H.265
- » Comparable to the DS-2CD2T42WD-I8

SPECIFICATIONS:

Туре	EXIR
Image Sensor	1/3 Inch Progressive Scan CMOS
Lens	2.8 mm, F2.0
Field of View	78.7 deg
Minimum Illumination	0.01 lux at F1.2 (AGC On), 0 lux with IR
Effective Pixels (H x V)	2688 x 1520
Video Compression	H.264/H.264+/H.265/H.265+/MJPEG
Shutter Speed	1/3 - 1/100000 sec
Day/Night	IR Cut Filter with Auto Switch
Speco DNR	3D DNR
Wide Dynamic Range	True WDR
Alarm Trigger	Motion Detection, Tampering Alarm, Network Disconnect, IP Address Conflict, Storage Exception
Frame Rate	2688 x 1520 at 30 fps
Communication Interface	(1) RJ-45 10/100 MB Ethernet Port
Supported Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPOE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, QoS
Functions	User Authentication, Reset Button, Flicker- less, Dual Stream, Heartbeat, Mirror, Watermark
Functions Network Storage	less, Dual Stream, Heartbeat, Mirror,
	less, Dual Stream, Heartbeat, Mirror, Watermark
Network Storage	less, Dual Stream, Heartbeat, Mirror, Watermark NAS
Network Storage Streams	less, Dual Stream, Heartbeat, Mirror, Watermark NAS Dual Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software
Network Storage Streams Image Settings	less, Dual Stream, Heartbeat, Mirror, Watermark NAS Dual Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser
Network Storage Streams Image Settings Reset Button	less, Dual Stream, Heartbeat, Mirror, Watermark NAS Dual Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Yes
Network Storage Streams Image Settings Reset Button Motion Detection	less, Dual Stream, Heartbeat, Mirror, Watermark NAS Dual Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Yes Yes
Network Storage Streams Image Settings Reset Button Motion Detection Power Supply	less, Dual Stream, Heartbeat, Mirror, Watermark NAS Dual Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Yes Yes 12 VDC +/-10%, PoE (802.3af)
Network Storage Streams Image Settings Reset Button Motion Detection Power Supply Power Consumption	less, Dual Stream, Heartbeat, Mirror, Watermark NAS Dual Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Yes Yes 12 VDC +/-10%, PoE (802.3af) 9.5 W Maximum
Network Storage Streams Image Settings Reset Button Motion Detection Power Supply Power Consumption Enclosure Rating	less, Dual Stream, Heartbeat, Mirror, Watermark NAS Dual Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Yes Yes 12 VDC +/-10%, PoE (802.3af) 9.5 W Maximum IP67
Network Storage Streams Image Settings Reset Button Motion Detection Power Supply Power Consumption Enclosure Rating IR Range	less, Dual Stream, Heartbeat, Mirror, Watermark NAS Dual Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Yes Yes 12 VDC +/-10%, PoE (802.3af) 9.5 W Maximum IP67 150 ft
Network Storage Streams Image Settings Reset Button Motion Detection Power Supply Power Consumption Enclosure Rating IR Range Mounting Type	less, Dual Stream, Heartbeat, Mirror, Watermark NAS Dual Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Yes Yes 12 VDC +/-10%, PoE (802.3af) 9.5 W Maximum IP67 150 ft Electrical Box
Network Storage Streams Image Settings Reset Button Motion Detection Power Supply Power Consumption Enclosure Rating IR Range Mounting Type Temperature Rating	less, Dual Stream, Heartbeat, Mirror, Watermark NAS Dual Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Yes Yes 12 VDC +/-10%, PoE (802.3af) 9.5 W Maximum IP67 150 ft Electrical Box -22 to 140 deg F (Operating)











