



PURPOSE AV - 4MP, EXIR TURRET, OUTDOOR, 2.8MM

SKU: HNC324-XD

FEATURES

- » 4 MP (2688 x 1520) Resolution
- » Full HD 4 MP real-time video
- » True WDR and 3D DNR and BLC
- » EXIR illuminator upto 100 ft
- » IP67
- » PoE
- » H.265
- » Comparable to the DS-2CD2342WD-I

SPECIFICATIONS:

Туре	EXIR
Image Sensor	1/3 Inch Progressive Scan CMOS
Lens	2.8 mm, F1.6
Field of View	78.7 deg
Minimum Illumination	0.01 lux at F1.2 (AGC On), 0 lux with IR
Effective Pixels (H x V)	2688 x 1520
Video Compression	H.264/H.264+/H.265/H.265+/MJPEG
Alarm Trigger	Motion Detection, Tampering Alarm
Frame Rate	2688 x 1520 at 30 fps
Shutter Speed	1/3 - 1/100000 sec
Speco DNR	3D DNR
Wide Dynamic Range	True WDR, 120 dB
Communication Interface	(1) RJ-45 10/100 MB Ethernet Port
Supported Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, QoS
System Compatibility	ONVIF, PSIA, CGI
Enclosure Rating	IP67
_	
Functions	User Authentication, Watermark
Functions IR Range	User Authentication, Watermark 100 ft
IR Range	100 ft
IR Range Mounting Type	100 ft Electrical Box/Wall/Pole/Corner
IR Range Mounting Type Angle Adjustment	100 ft Electrical Box/Wall/Pole/Corner Pan: 0 - 355 deg, Tilt: 0 - 75 deg
IR Range Mounting Type Angle Adjustment Network Storage	100 ft Electrical Box/Wall/Pole/Corner Pan: 0 - 355 deg, Tilt: 0 - 75 deg NAS
IR Range Mounting Type Angle Adjustment Network Storage Backlight Compensation	100 ft Electrical Box/Wall/Pole/Corner Pan: 0 - 355 deg, Tilt: 0 - 75 deg NAS Yes (Zone Configurable)
IR Range Mounting Type Angle Adjustment Network Storage Backlight Compensation Bit Rate	100 ft Electrical Box/Wall/Pole/Corner Pan: 0 - 355 deg, Tilt: 0 - 75 deg NAS Yes (Zone Configurable) 32 kbps - 16 Mbps
IR Range Mounting Type Angle Adjustment Network Storage Backlight Compensation Bit Rate Motion Detection	100 ft Electrical Box/Wall/Pole/Corner Pan: 0 - 355 deg, Tilt: 0 - 75 deg NAS Yes (Zone Configurable) 32 kbps - 16 Mbps Yes Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software
IR Range Mounting Type Angle Adjustment Network Storage Backlight Compensation Bit Rate Motion Detection Image Settings	100 ft Electrical Box/Wall/Pole/Corner Pan: 0 - 355 deg, Tilt: 0 - 75 deg NAS Yes (Zone Configurable) 32 kbps - 16 Mbps Yes Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser
IR Range Mounting Type Angle Adjustment Network Storage Backlight Compensation Bit Rate Motion Detection Image Settings	100 ft Electrical Box/Wall/Pole/Corner Pan: 0 - 355 deg, Tilt: 0 - 75 deg NAS Yes (Zone Configurable) 32 kbps - 16 Mbps Yes Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Triple
IR Range Mounting Type Angle Adjustment Network Storage Backlight Compensation Bit Rate Motion Detection Image Settings Streams Power Supply	100 ft Electrical Box/Wall/Pole/Corner Pan: 0 - 355 deg, Tilt: 0 - 75 deg NAS Yes (Zone Configurable) 32 kbps - 16 Mbps Yes Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Triple 12 VDC +/-10%, PoE (802.3af)
IR Range Mounting Type Angle Adjustment Network Storage Backlight Compensation Bit Rate Motion Detection Image Settings Streams Power Supply Power Consumption	100 ft Electrical Box/Wall/Pole/Corner Pan: 0 - 355 deg, Tilt: 0 - 75 deg NAS Yes (Zone Configurable) 32 kbps - 16 Mbps Yes Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Triple 12 VDC +/-10%, PoE (802.3af) 7.5 W Maximum
IR Range Mounting Type Angle Adjustment Network Storage Backlight Compensation Bit Rate Motion Detection Image Settings Streams Power Supply Power Consumption Temperature Rating	100 ft Electrical Box/Wall/Pole/Corner Pan: 0 - 355 deg, Tilt: 0 - 75 deg NAS Yes (Zone Configurable) 32 kbps - 16 Mbps Yes Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser Triple 12 VDC +/-10%, PoE (802.3af) 7.5 W Maximum -22 to 140 deg F (Operating)











