PURPOSE

OUR PURPOSE CHANGING THE LIVES OF YOUTH THROUGH CHARITABLE GIVING



PURPOSE AV - 4MP, EXIR TURRET, OUTDOOR, 2.8 MM (GREY)

SKU: HNC324-XDB-2.8

FEATURES

- » 4 MP (2688 x 1520) Resolution
- » Grey Housing
- » Full HD 4 MP real-time video
- » True WDR and 3D DNR and BLC
- » EXIR illuminator upto 100 ft
- » IP67
- » PoE
- » H.265
- » Comparable to the DS-2CD2342WD-I

















GIVES BACK



Staub Electronics Ltd. is our exclusive distribution partner in North America. For product or sales inquiries please contact them as follows: **Phone:** +1 (604) 270-7316 **Email:** support@purposeav.ca Web: www.staub.ca

SPECIFICATIONS:

Туре	EXIR, Exterior
Image Sensor	1/3 Inch Progressive Scan CMOS
Lens	2.8 mm, F1.6
Field of View	78.7 deg
Minimum Illumination	0.01 lux at F1.2 (AGC On), 0 lux with IR
Effective Pixels (H x V)	2688 x 1520
Video Compression	H.264/H.264+/H.265/H.265+/MJPEG
Alarm Trigger	Motion Detection, Tampering Alarm
Frame Rate	2688 x 1520 at 30 fps
Shutter Speed	1/3 - 1/100000 sec
Speco DNR	3D DNR
Wide Dynamic Range	True WDR, 120 dB
Communication Interface	(1) RJ-45 10/100 MB Ethernet Port
Supported Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPOE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, QoS
System Compatibility	ONVIF, PSIA, CGI
Enclosure Rating	IP67
Functions	User Authentication, Watermark
IR Range	100 ft
Mounting Type	Electrical Box/Wall/Pole/Corner
Angle Adjustment	Pan: 0 - 355 deg, Tilt: 0 - 75 deg
Network Storage	NAS
Backlight Compensation	Yes (Zone Configurable)
Bit Rate	32 kbps - 16 Mbps
Motion Detection	Yes
Image Settings	Saturation, Brightness, Contrast, Sharp- ness Adjustable Through Client Software Or Web Browser
Streams	Triple
Power Supply	12 VDC +/-10%, PoE (802.3af)
Power Consumption	7.5 W Maximum
Temperature Rating	-22 to 140 deg F (Operating)
Relative Humidity	95% or Less Non-Condensing
Color	Grey (Housing)
Dimensions	5 Inch Dia x 3.8 Inch H
Weight	1.5 lb