



OUR PURPOSE

CHANGING THE LIVES OF YOUTH
THROUGH CHARITABLE GIVING



PURPOSE AV - 4MP, MOTORIZED IR TURRET, OUTDOOR, 2.8-12MM, PIGTAIL FREE

SKU: HNC324-XDZ

FEATURES

- » 4 MP (2688 x 1520) Resolution
- » Full HD 4 MP real-time video
- » True WDR and 3D DNR and BLC
- » EXIR illuminator upto 100 ft
- » IP67, IK10
- » PoE
- » H.265
- » Comparable to the DS-2CD2H43G0-IZS

SPECIFICATIONS:

Type	EXIR, Exterior
Image Sensor	1/3 Inch Progressive Scan CMOS
Lens	2.8 - 12 mm, F1.6 (Motorized Varifocal)
Field of View	98 - 28 deg
Minimum Illumination	0.01 lux at F1.2 (AGC On), 0 lux with IR
Effective Pixels (H x V)	2688 x 1520
Video Compression	H.264/H.264+/H.265/H.265+/MJPEG
Alarm	1 In/1 Out
Alarm Trigger	Motion Detection, Tampering Alarm
Frame Rate	2688 x 1520 at 20 fps
Shutter Speed	1/3 - 1/100000 sec
Speco DNR	3D DNR
Wide Dynamic Range	True WDR, 120 dB
Audio	1 In/1 Out
Communication Interface	(1) RJ-45 10/100 MB Ethernet Port
Supported Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, QoS
System Compatibility	ONVIF, PSIA, CGI
Enclosure Rating	IP67, IK10
Functions	User Authentication, Watermark
IR Range	100 ft
Mounting Type	Wall/Pendant/Corner/Pole
Angle Adjustment	Pan: 0 - 355 deg, Tilt: 0 - 75 deg
Network Storage	NAS
Backlight Compensation	Yes (Zone Configurable)
Streams	Dual
Bit Rate	32 kbps - 16 Mbps
Motion Detection	Yes
Image Settings	Saturation, Brightness, Contrast, Sharpness Adjustable Through Client Software Or Web Browser
Power Supply	12 VDC +/-10%, PoE (802.3af)
Power Consumption	10 W Maximum (12.5 W with ICR On)
Temperature Rating	-22 to 140 deg F (Operating)
Relative Humidity	95% or Less Non-Condensing



100% PERFORMANCE
GUARANTEE



DAILY IN-STOCK
PROMISE



SEAMLESS
SUPPORT



10 YEAR
WARRANTY



GIVES BACK
TO CHARITY

STAUB
ELECTRONICS

Staub Electronics Ltd. is our exclusive distribution partner in North America. For product or sales inquiries please contact them as follows:

Phone: +1 (604) 270-7316

Email: support@purposeav.ca

Web: www.staub.ca