



PURPOSE AV - 8MP, EXIR DOME, OUTDOOR, 2.8MM

SKU: HNC328-TD

FEATURES

- » 8 MP (3840 x 2160) Resolution
- » Full HD 5 MP real-time video
- » 3D DNR, True WDR, BLC
- » IP67 and IK10 Rating
- » PoE
- » Vandal-proof
- » Comparable to the DS-2CD2185FWD-I

SPECIFICATIONS:

Image Sensor	1/2.5" progressive scan CMOS
Lens	4mm @ F1.2, angle of view: 102° / Optional 2.8mm, 6mm
Minimum Illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter Time	1/3s ~ 1/100,000s
Angle Adjustment	Pan: -90° ~ 90°, tilt 0° ~ 75°, Rotation: 0-355°
DNR	3D DNR
Wide Dynamic Range	True WDR
Day & Night	ICR
Video Compression	H.265 / H.264+ / H.264 / MJPEG
Dual Stream	Yes
Max. Image Resolution	3840×2160
Frame Rate	15fps (3840×2160), 30fps (2944×1656), 30fps (2560×1920), 30fps (1920×1080)
Image Settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
On-Board Storage	Micro SD slot, up to 128GB
Network Storage	Support microSD/SDHC/SDXC card (128G) local storage, NAS (NFS, SMB/CIFS), ANR
Alarm Trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System Compatibility	ONVIF, PSIA, CGI
Operating Conditions	-30° C ~ 60° C (-22° F ~ 140° F) humidity 90% or less (non-condensing)
Power Supply	12 VDC +/- 10%, PoE (802.3af)
Power Consumption	Max, 9W
Ratings	IP67 / IK10
IR Range	Up to 90ft
Dimensions	Ø 4.4"x3.2"











