



PURPOSE AV - 8MP, EXIR MINI BULLET, OUTDOOR, 2.8MM

SKU: HNC328-MB

FEATURES

- » 8 MP High Resolution
- » Full HD Video Output
- » Low Illumination
- » 3D DNR; True WDR; BLC
- » IP67 Rating
- » IR Range: upto 100 ft
- » True Day/Night
- » Comparable to the DS-2CD2085FWD-I

SPECIFICATIONS:

Туре	Mini
Image Sensor	1/2.5 Inch Progressive Scan CMOS
Lens	2.8 mm, F2.0
Field of View	102 deg
Minimum Illumination	0.01 lux at F1.2 (AGC On), 0 lux with IR
Effective Pixels (H x V)	3840 x 2160
Video Compression	H.264/H.264+/H.265/MJPEG
Shutter Speed	1/3 - 1/100000 sec
Day/Night	IR Cut Filter with Auto Switch
Speco DNR	3D DNR
Wide Dynamic Range	True WDR
Alarm Trigger	Motion Detection, Tampering Alarm, Network Disconnect, IP Address Conflict, Storage Exception
Frame Rate	15 fps (3840 x 2160), 30 fps (2560 x 1920)
Communication Interface	(1) RJ-45 10/100 MB Ethernet Port
Supported Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPOE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, QoS
Functions	User Authentication, Reset Button, Flicker- less, Dual Stream, Heartbeat, Mirror, Watermark
On-Board Storage	128 GB SD Card Slot
Image Settings	Saturation, Brightness, Contrast, Sharp- ness Adjustable Through Client Software Or Web Browser
Power Supply	12 VDC +/-10%, PoE (802.3af)
Power Consumption	7 W Maximum
Enclosure Rating	IP67
IR Range	100 ft
Mounting Type	Electrical Box
Temperature Rating	-22 to 140 deg F (Operating)
Relative Humidity	90% or Less Non-Condensing
Dimensions	2.76 Inch Dia x 6.1 Inch H
Weight	0.9 lb











