PURPOSE

OUR PURPOSE CHANGING THE LIVES OF YOUTH THROUGH CHARITABLE GIVING



PURPOSE AV - 4MP, IR FIX DOME, **OUTDOOR, 2.8MM**

SKU: HNC344-TD-2.8

FEATURES

- » 4 MP (2688 x 1520) resolution
- » Full HD 4 MP real-time video
- » Smart Sense
- » IP67 and IK10 Rating
- » PoE
- » Vandal-proof
- » H.265
- » Comparable to DS-2CD2146G1-I















GIVES BACK TO CHARITY



Staub Electronics Ltd. is our exclusive distribution partner in North America. For product or sales inquiries please contact them as follows: Phone: +1 (604) 270-7316 Email: support@purposeav.ca Web: www.staub.ca

SPECIFICATIONS:

Туре	Mini, Exterior
Image Sensor	1/2.7 Inch Progressive Scan CMOS
Lens	2.8 mm at F1.2 (Fixed)
Minimum Illumination	0.007 lux at F1.2 (AGC On), 0 lux with IR
Effective Pixels (H x V)	2688 x 1520
Video Compression	H.264/H.264+/H.265/H.265+/MJPEG
Alarm Trigger	Tampering Alarm, Network Disconnected, IP Address Conflict, Illegal Login, HDD Full, HDD Error
Frame Rate	30 fps (2688 x 1520)
Shutter Speed	1/3 - 1/100000 sec
Day/Night	ICR
Speco DNR	3D DNR
Wide Dynamic Range	True WDR, 120 dB
Supported Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPP0E, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, QoS
Functions	User Authentication, Watermark
IR Range	Up to 90 ft
Mounting Type	Wall/Pendant/Pole/Corner
Angle Adjustment	Pan: 0 - 355 deg, Tilt: 0 - 75 deg, Rotation: 0 - 355 deg
Streams	Triple
Protection Level	IK10
On-Board Storage	Micro SD Slot, Up to 128 GB
Communication Interface	(1) RJ-45 10M/100M Ethernet Port
Enclosure Rating	IP67
Image Settings	Saturation, Brightness, Contrast, Sharp- ness Adjustable Through Client Software or Web Browser
System Compatibility	ONVIF (Profile S, Profile G), ISAPI
Power Supply	12 VDC +/-10%, PoE (802.3af, Class 3)
Power Consumption	8.5 W Maximum
Temperature Rating	-22 to 122 deg F
Relative Humidity	95% or Less (Non-Condensing)
Dimensions	4.8 Inch Dia x 3.6 Inch H
Weight	1.3 lb