

Paging Horn Speaker

HS-50



OVERVIEW

The HS-50 is a double re-entrant loudspeaker which delivers 50-watts of continuous power handling.

The HS-50 has operates within a nominal frequency response range of 380Hz to 6,5K Hz and offers a sensitivity of 109 dB at 1 watt, 1 meter to provide clear voice intelligibility, signal communication and efficiency.

Robust weather-resistant aluminium construction and finished in grey epoxy for reliability both indoor and outdoor use.

FEATURES

- Excellent intelligibility & Loudness for Voice and Tone Signaling
- High directivity,
- Good reliability
- Environment Resistant for Outdoor and Indoor Use
- Grey Finish
- High-Efficiency Driver with Proven Performance
- Transformer Equipped for Versatile 25, 70.7, or 100V Line Applications

SPECIFICATIONS

Spec	Model	Unit	HS-50
Rated Input		W	50
Impedance		Ω	200, 400
Frequency Response		Hz	380 ~ 6.5k
70V watts		W	25, 12.5
100V watts		W	50, 25
SPL (1W/m)		dB	109
IP Ratings		IP	54
Operating Temperature, Dust and Humidity		$^{\circ}\text{C}$	-45 ~ 50
		$^{\circ}\text{F}$	-49 ~ 122
Weight		kg	3.1
		lb	6.8
Dimensions (W×H×D)		mm	ø320x350
		inches	ø12.6x13.7


* Specifications and design are subject to change without notice.



APPLICATION


Our technology can be found in schools, hospitals, malls, campus, transportation, correctional facilities, recreational facilities and a variety of commercial and industrial applications.

Polar Pattern Diagram



Frequency Response

► SPL DATA



Inter-M Corporation

- Office : 653-5 BANGHAK-DONG, DOBONG-KU, SEOUL, KOREA
 - Tel : +82-2-2289-8140~8, Fax : +82-2-2289-8149
 - Home page: <http://www.inter-m.com>, E-mail: overseas@inter-m.com

Inter-M Corporation (USA)

- Office : 14730 E. FIRESTONE BLVD #312 LA MIRADA, CA 90638
 - Tel : +1-714-523-1870, Fax : +1-714-523-1882
 - Home Page : <http://www.inter-m.net>, E-mail : info@inter-m.net