



LCR 60 & 30'S

The Composer Collection complements the room with a modern and slim bezel-less frame. Regardless of form, the fit and finish of Origin speakers are as clean and impressive as their sound quality. Once installed the speakers become a part of the environment where they disappear unless, of course, your pride of ownership moves you to point them out.



LCR69



LCR67



LCR65



LCR39



LCR37

IN DETAIL

■ DPSD™ Tweeter

This patented tweeter has the greatest output and is able to crossover much lower to either the woofer or the midrange improving both dispersion and the frequency response.

■ Woofer Cone Materials

Designed from the ground up, we only use the finest materials for our woofers to ensure optimal performance in response with speed and precision.

■ Compression Molded Baskets

These complex baskets that support the woofer cones were computer designed and compression molded with absolute precision allowing for unique support and venting elements to assure peak performance.

■ EQ Adjustment

These switches on the baffle allows the adjustment of the output of either the high frequencies or both high and low frequencies to custom tailor the sound based on the proximity of the architectural elements of the room.

■ Tool-less Mounting System

The Spring-Lock™ mounting dogs are spring loaded and require only a twist with a thumbnail to have them snap easily and securely into place.

■ X-Wave™ Woofer Surround

This suspension element absorbs unwanted frequencies that reflect up and down the woofer cone to reduce harmonic distortion while maintaining the desired linear travel of the woofer.

SPECIFICATIONS

| MODEL | LCR69 | LCR67 |
|--------------------|-------------------------------|-------------------------------|
| PART | SWML14900 | SWML14700 |
| Woofer | 2 x 6 1/2" Kevlar® | 2 x 6 1/2" Glass Fiber |
| Tweeter | 1" Silk DPSD™ | 1" Silk DPSD™ |
| Frequency Response | 51Hz-20kHz | 53Hz-20kHz |
| Power RMS | 40 Watts | 40 Watts |
| Power Peak | 150 Watts | 150 Watts |
| Impedance | 6 ohm | 6 ohm |
| Dimensions | 7 1/2 x 15 1/4" (190 x 386mm) | 7 1/2 x 15 1/4" (190 x 386mm) |
| Cutout Dimensions | 6 5/8 x 14 3/8" (168 x 364mm) | 6 5/8 x 14 3/8" (168 x 364mm) |
| Grille Dimensions | 7 7/8 x 15 5/8" (200 x 403mm) | 7 7/8 x 15 5/8" (200 x 403mm) |
| Mounting Depth | 3 3/4" (95mm) | 3 3/4" (95mm) |

| MODEL | LCR65 | LCR39 | LCR37 |
|--------------------|-------------------------------|----------------------------------|----------------------------------|
| PART | SWML14500 | SWML10900 | SWML10700 |
| Woofer | 2 x 6 1/2" IMG | 2 x 3 1/2" Kevlar® | 2 x 3 1/2" Fiber Glass |
| Tweeter | 1" Silk DPSD™ | 1" Silk DPSD™ | 1" Silk DPSD™ |
| Frequency Response | 55Hz-20kHz | 70Hz-20kHz | 70Hz-20kHz |
| Power RMS | 40 Watts | 35 Watts | 35 Watts |
| Power Peak | 150 Watts | 125 Watts | 125 Watts |
| Impedance | 6 ohm | 6 ohm | 6 ohm |
| Dimensions | 7 1/2 x 15 1/4" (190 x 386mm) | 5 1/4 x 10 1/4" (134 x 262mm) | 5 1/4 x 10 1/4" (134 x 262mm) |
| Cutout Dimensions | 6 5/8 x 14 3/8" (168 x 364mm) | 4 3/8 x 9 1/2" (122 x 240mm) | 9 1/8 x 10 1 1/16" (144 x 272mm) |
| Grille Dimensions | 7 7/8 x 15 5/8" (200 x 396mm) | 9 1/8 x 10 1 1/16" (144 x 272mm) | 9 1/8 x 10 1 1/16" (144 x 272mm) |
| Mounting Depth | 3 3/4" (95mm) | 3 3/4" (95mm) | 3 3/4" (95mm) |

