

## **UTBUS-1xI**

Under-the-Table Modular Multi-Connection Solution Enclosure

| VGA/UXGA - 15-pin HD



The UTBUS-1xl is the enclosure of a new modular system. A complete UTBUS system requires the enclosure, a power socket, inserts and a power cord.

NOTE: The UTBUS enclosure, power socket, power cord & inserts are purchased separately

## **FEATURES**

Power Sockets - 8 different "TS" single power socket options are available to accommodate the power requirements worldwide

Power Cord - 8 different "C-AC" single power cords for each power socket

Insert Slots - 6

Installation Requirement - Requires 29.0cm x 13.7cm (11.4in x 5.4in) of free space beneath the table Weight - 0.6kg (1.32lbs) approx



## TECHNICAL SPECIFICATIONS

POWER SOURCE Universal: 100-240V AC, 50/60Hz, 5A; USA: 100-240V AC, 50/60Hz, 5A; UK:

(AC power limits): 100-240V AC, 50/60Hz, 5A; Germany and EU: 100-240V AC, 50/60Hz, 5A;

Belgium and France: 100-240V AC, 50/60Hz, 5A; South Africa: 100-240V AC,

50/60Hz, 5A; Australia: 100-240V AC, 50/60Hz, 5A

FUSE RATING: T 6.3A 250V

INCLUDED ACCESSORIES:

Self locking ties, wood screws

OPTIONS: Passive wall plate inserts and interfaces, power cord

Product Dimensions 27.50cm x 10.20cm x 6.50cm (10.83" x 4.02" x 2.56") W, D, H

Product Weight 2.0kg (4.4lbs) approx

Shipping Dimensions 34.00cm x 24.80cm x 9.70cm (13.39" x 9.76" x 3.82") W, D, H

Shipping Weight 2.0kg (4.4lbs) approx