



The WattBox Family of IP-Controlled Power Strips & Conditioners

WattBox® power products are not your average power strips. They're uniquely designed with three lines of defense and individual outlet control, so you can stop rebooting and start relaxing.

THREE LINES OF DEFENSE

SELF-HEALING AUTO-REBOOT

WattBox IP units continuously monitor connectivity, and when connection is lost, automatically reboots the troubled device as programmed.

MOBILE APP

A free mobile app, included with all WattBox IP products, allows you to reset any device connected to individual outlets, and easily contact your integrator for additional help.



PROTECT YOUR INVESTMENT

Pair your WattBox power product with a WattBox Uninterruptible Power Supply. Our UPS is the world's most sophisticated battery backup – packed with features to keep your equipment up and running in case of power loss.



REMOTE MANAGEMENT

WattBox comes with an advanced remote management platform, allowing your integrator to remotely reboot devices, modify configurations, update firmware, and more. It even notifies them if a WattBox goes offline or its voltage falls outside a safe range.

FORM FACTORS FOR EVERY INSTALL

No matter your job, WattBox has a product to match. Our WB-150 and 3 and 5-outlet models are perfect for tight spaces, while 12 & 18-outlet designs help make for an organized rack.

| | 800 IPVM Series | | 700 IPV Series | | 300 IP Series | | 150 IP Series |
|------------------------------|----------------------|----------------------|-----------------|---------------|------------------|--------------|---------------------|
| Models | WB-800VPS-IPVM-18 | WB-800VPS-IPVM-12 | WB-700CH-IPV-12 | WB-700-IPV-12 | WB-300VB-IP-5 | WB-300-IP-3 | WB-150-IP-1B-2 |
| Number of Outlet Options | 18 | 12 | 12 | 12 | 5 | 3 | 2 |
| Individual IP Outlet Control | ● | ● | ● | ● | ● | ● | 1 Bank of 2 Outlets |
| Individual Outlet Metering | ● | ● | Total Only | Total Only | Total Only | Total Only | |
| Wi-Fi Connectivity | | | | | | | |
| Ethernet Connectivity | ● | ● | ● | ● | ● | ● | ● |
| Form Factor | 50.5" Vertical Strip | 36.5" Vertical Strip | 2U Chassis | 2U Rackmount | Drop-In Versabox | Compact/Slim | Ultra-Compact |
| Peak Current Rating | 15A | 15A | 15A | 15A | 15A | 15A | 15A |
| Voltage Rating | 120V | 120V | 120V | 120V | 120V | 120V | 120V |
| Surge Joule Rating | 3240J | 3240J | 3240J | 3240J | 3240J | 3240J | 2160J |
| Power Conditioning (EMI/RF) | ● | ● | ● | ● | | | |
| UL Certified | ● | ● | ● | ● | ● | ● | ● |
| Safe Voltage | ● | ● | ● | ● | | | |
| OvrC UPS/Battery Backup Link | ● | ● | ● | ● | ● | ● | |
| Detachable IEC Power Cord | ● | ● | ● | ● | ● | ● | ● |
| Trigger Input Port | | | ● | ● | ● | ● | |
| Volt/ Amp FacePlate | | | ● | ● | | | |
| Remote Firmware Upgrades | ● | ● | ● | ● | ● | ● | ● |
| Self-healing Auto-Reboot | ● | ● | ● | ● | ● | ● | ● |
| Scheduled Power Cycles | ● | ● | ● | ● | ● | ● | ● |
| Remote Management | ● | ● | ● | ● | ● | ● | ● |
| Mobile End-User App | ● | ● | ● | ● | ● | ● | ● |
| Local Control API | ● | ● | ● | ● | ● | ● | ● |
| Control Drivers | | | | | | | |
| Control 4 | ● | ● | ● | ● | ● | ● | ● |
| RTI | ● | ● | | | ● | ● | ● |
| Elan | ● | ● | | | ● | ● | ● |
| URC | ● | ● | | | ● | ● | ● |
| Creston | ● | ● | ● | ● | ● | ● | ● |