

WATT BOX

COMPARISON CHART



SURGE & CONDITIONING

Model	WB-200-2	WB-200-CE-4	WB-400-8	WB-400-CE-10	WB-400-VCE-12	WB-600-VCE-10	WB-600-SVCE-12	WB-600CH-SVCE-12
Outlets	2	4	8	10	12	10	12	12
Power Cord Length	1.5 FT	4 FT	6FT	6FT	6FT	6FT	6FT	6FT
Rack Mountable	N	N	Y	Y	Y	Y	Y	Y
Energy Disipation	2160 Joules	2160 Joules	3240 Joules	3240 Joules	4320 Joules	5400 Joules	6480 Joules	6480 Joules
Fireproof MOV	Y	Y	Y	Y	Y	Y	Y	Y
Isolated Filter Banks	1	1	1	1	2	2	3	3
Coax Protection	No	1 In - 1 Out	No	2 In - 2 Out	2 In - 2 Out	2 In - 2 Out	2 In - 2 Out	2 in - 2 Out
Telephone/Network Protection	No	1 In - 1 Out	No	1 In - 1 Out	1 In - 1 Out	1 In - 1 Out	2 In - 2 Out	2 in - 2 Out
Safe Voltage	N	N	N	N	Y	Y	Y	Y
12V Trigger	N	N	N	N	N	In	In/Out	In/Out
Sequencing	N	N	N	N	N	N	Y	Y
Optional Faceplate Display	N	N	N	N	N	Y	Y	Y
Connected Equipment Warranty	\$25,000	\$25,000	\$50,000	\$50,000	\$50,000	\$50,000	\$50,000	\$50,000
UL Listed	Y	Y	Y	Y	Y	Y	Y	Y

* Specs subject to change without notice